



Special Order Information
31-1010 Crankcase, Assembly, Cast, Pro Stock, SA
Please fax this form to 608-627-1488 when completed

Date _____

Dealer # _____

Dealer Name: _____ Ordered by: _____

E mail address: _____

Phone # _____ Fax # _____

Please complete this form and return it to S&S Cycle Inc. so your special order parts can be processed. This form will ensure that your order will be placed correctly and the crankcases produced to your specifications. Items ordered per this form must be paid in full before production. Any specifications other than those listed will require a drawing or blueprint, and will only be able to be ordered from November 1st through March 1st.

Check the box in each area that describes your specific application

Quantity: _____

Include Breather Mount:

- Yes, Include Breather Mount **(REQUIRES 31-0300 OR 31-0303 GEAR COVER)**
- No, Don't Include Breathe Mount **(REQUIRES 31-0301 GEAR COVER)**

Cylinder Base/Stud Pattern:

- S&S 4.375" Steel
- S&S 4.375" Aluminum
- S&S 4.375" Tribute
- S&S 4.600" Steel/Aluminum
- S&S 4.800" Steel/Aluminum

Spigot Bore Size:

- 4.635" S&S 4.375" Bore
- 4.815" S&S 4.600" Bore
- 5.015" S&S 4.800" Bore
- Unfinished
- Specify

Specify Spigot Bore Size: (Option only if specify spigot bore size is chosen)

- 4.635" - 5.015" _____ (Specify)

Cam Geometry:

- 86-90 Cam Geometry
- 91-99 Cam Geometry **(no tappet guides supplied)**



Install Studs:

- Yes, Install Studs*
- No, Don't Install but Include*
- No, Don't Install or Include*

Cylinder Stud/Bolt Type: (N/A if No Don't Install or Include Studs is Chosen)

- 50-0160 Screw,SHC,3/8-16 x 1-1/2",Plain,Steel*
- 50-0173 Screw,SHC,7/16-14 x 1-1/2",Black,ASTM A574-92A*
- 50-0174 Screw,SHC,Gr8,7/16-14 x 1-3/4",Black,ASTM A574-92A*
- 31-2331-S Stud,Cylinder Base,3/8-16 UNC x 5.760"*
- 31-2332-S Stud,Cylinder Base,3/8-16 ONF, 3/8-24 UNF x 2.770,Black,Steel*
- 31-2324-S Stud,Cylinder Base,7/16-14 ONF, 7/16-20 UNF x 2.3,Black,Steel*
- 31-2325-S Stud,Cylinder Base,3/8-16 UNC x 6.070",Black,Steel*
- 31-2328-S Stud,Cylinder Base,7/16-14 UNC, 7/16-20 UNF x 2.0,Zinc,Steel*
- 50-8086 Stud,3/8-24 UNF, 3/8-16 ONF x 2.312,Zinc*
- 31-2321-S Stud,Cylinder Base,6.68",Black Oxide*

Crankcase Deck Height (from crankshaft center):

- 6.000" – 7.125" _____ (Specify)*

Spigot Bore Depth: (Max Spigot Depth Can't be Less Than 3.700" From Case Center)

- _____ (Specify)

Flywheel Diameter:

- 7.875"*
- 8.125"*

Machine for transmission:

- Yes*
- No*

Machine for transmission window:

- Yes*
- No*

Machine for speed sensor:

- Yes*
- No*

Machine for starter hole:

- Yes (default to yes if no to transmission window)*
- No (default to no if yes to transmission window)*

Comments: _____

