



**Special Order Information**  
**16-2539 Manifold, Super G, 2-1/16",**  
**VOES, 1984-up bt**  
Please fax this form to 608-627-1488 when completed

Date \_\_\_\_\_ Dealer # \_\_\_\_\_

Dealer Name: \_\_\_\_\_ Ordered by: \_\_\_\_\_

E mail address: \_\_\_\_\_

Phone # \_\_\_\_\_ Fax # \_\_\_\_\_

*Please complete this form and return it to S&S Cycle Inc. so your special order parts can be processed. This form will ensure that your order will be placed correctly and the manifolds produced to your specifications. Items ordered per this form must be paid in full before production. Any specifications other than those listed will require a drawing or blueprint, and will only be able to be ordered from November 1<sup>st</sup> through March 1<sup>st</sup>.*

Check the box in each area that describes your specific application

Quantity: \_\_\_\_\_

How is the manifold measured:

- Port Center – Port Center Engine
- Port Center – Port Center Manifold
- Engine Component Measurements
- Port – Port Shortest Port Distance
- Port – Port Engine Shortest Distance
- Manifold Size Number
- S&S Measurement Tools

Case Deck Height: (Option only if engine component measurements chosen)

- Stock EVO (5.375")
- Stock TC (6.000")
- S&S 4" SA (5.875")
- S&S SSW+ 4-1/8" Bore (6.000")
- Other

Case Deck Height Adjustment: (Option only if engine component measurements chosen)

- 0.000" – 0.625" \_\_\_\_\_ (Specify)

Base Plate: (Option only if engine component measurements chosen)

- 0.000" – 0.500" \_\_\_\_\_ (Specify)

Cylinder Length: (Option only if engine component measurements chosen)

- 2.500" – 6.750" \_\_\_\_\_ (Specify)

Heads Decked: (Option only if engine component measurements chosen)

- 0.000" – 0.200" \_\_\_\_\_ (Specify)



Ports Raised: **(Option only if engine component measurements chosen)**

0.000" – 0.750" \_\_\_\_\_ (Specify)

Effective Cylinder Length: **(Option only if engine component measurements chosen)**  
**((deck adjustment + base plate) + (cylinder length – heads decked + ports raised))**

\_\_\_\_\_ (Specify)

Manifold Size Code: **(Option only if manifold size number measurement is chosen)**

387 – 487 \_\_\_\_\_ (Specify)

Port to Port Distance: **(Option only if any of the port measurements are chosen)**

3.870" – 4.870" \_\_\_\_\_ (Specify)

Machine for MAP Sensor:

Machine for MAP Sensor

Don't Machine for MAP Sensor

Remove MAP Boss Machining: **(Option only if Don't Machine MAP Sensor is chosen)**

Remove MAP Boss Machining

Don't Remove MAP Boss Machining

Extra Vacuum Nipple:

Machine Extra Vacuum Nipple

Don't Machine Extra Vacuum Nipple

Measurement from S&S tool: **(Option only if S&S measurement tools is chosen)**

\_\_\_\_\_ (Specify)

Comments: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_