



Special Order Information
31-0023A Crankcase, Assembly, Alt/Gen, 1970-'99 Custom
Please fax this form to 608-627-1488 when completed

Date _____

Dealer # _____

Dealer Name: _____ Ordered by: _____

E mail address: _____

Phone # _____ Fax # _____

Please complete this form and return it to S&S Cycle Inc. so your special order parts can be processed. This form will ensure that your order will be placed correctly and the crankcases produced to your specifications. Items ordered per this form must be paid in full before production. Any specifications other than those listed will require a drawing or blueprint, and will only be able to be ordered from November 1st through March 1st.

Check the box in each area that describes your specific application

Quantity: _____

Color:

- Natural*
 Polished

****IF YOU CHOOSE POLISHED CASES YOU ARE ASSUMING THE RISK THAT THE POLISHING PROCESS MAY REVEAL COSMETIC POROSITY OR OTHER SURFACE DEFECTS IN THE CASTINGS. S&S DOES NOT GUARANTEE A PERFECT FINISH****

Customer agrees to polish disclaimer:

- Yes*

Crankcase Right Side:

- 36-47 Knuckle Style*
 45-64 Pan
 65-69 Pan/Shovel

Relay Mount Boss:

- Include Relay Mount Boss*
 Don't Include Relay Mount Boss

Flywheel Diameter:

- 8.250"*
 8.500"



Cylinder Base Stud Pattern:

- Stock Evolution®*
- Knuckle*
- Pan*
- Shovel*
- S&S 3-13/16" Expanded*
- No Base Pattern*

Spigot Bore Size:

- 3.683" for Stock Bore*
- 3.879" for S&S 3-5/8" Bore*
- 3.980" for S&S 3-13/16" Expanded*

Case Deck Height:

- 5.375"*
- 5.5625" (+.1875")*

Top End Oil Feed Holes: (Option only for pan or pan/shovel)

- Drill Oil Feed in Cylinder Base*
- Don't Drill Oil Feed Holes*

Oil Pump Year:

- 1981-1991*
- 1992-1999*
- Stock Generator (36-69)*

Install Studs:

- Yes, Install Studs*
- No, Don't Install but Include*
- No, Don't Install or Include*

Cylinder Stud/Bolt Type: (N/A if No Don't Install or Include Studs is Chosen)

- 50-0160 Screw, SHC, 3/8-16 x 1-1/2", Plain, Steel*
- 50-0173 Screw, SHC, 7/16-14 x 1-1/2", Black, ASTM A574-92A*
- 31-2331-S Stud, Cylinder Base, 3/8-16 UNC x 5.760"*
- 31-2324-S Stud, Cylinder Base, 7/16-14 ONF, 7/16-20 UNF x 2.3, Black, Steel*
- 31-2325-S Stud, Cylinder Base, 3/8-16 UNC x 6.070", Black, Steel*
- 31-2328-S Stud, Cylinder Base, 7/16-14 UNC, 7/16-20 UNF x 2.0, Zinc, Steel*
- 31-2321-S Stud, Cylinder Base, 6.68", Black Oxide*

Comments: _____

