

Special Order Information
90-1452 Cast Pro Stock Heads
Please fax this form to 608-627-1488 when completed



Date _____

Dealer # _____

Dealer Name: _____ Ordered by: _____

E mail address: _____

Phone # _____ Fax # _____

Please complete this form and return it to S&S Cycle Inc. so your special order parts can be processed. This form will ensure that your order will be placed correctly and the heads produced to your specifications. Items ordered per this form must be paid in full before production. Any specifications other than those listed will require a drawing or blueprint, and will only be able to be ordered from November 1st through March 1st.

Check the box in each area that describes your specific application

Quantity: _____

Pushrod Holes:

- S&S Pro Stock*
- SA Twin Cam*
- Other*
- No Machining*

Pro Stock Head Bolt Pattern:

- S&S 4.800"*
- S&S 4.600"*
- None*

Port Machining:

- Yes*
- No*

Flange Style:

- Weld On Style Flange*
- Street Pro Style Flange*

Chamber Machining:

- S&S Chamber Machining*
- No Chamber Machining*

Seat Pocket Machining: (Only ask if S&S Chamber Machining is Chosen)

- Normal Machining Seat Pocket*
- No Seat Pocket Machining*



Machine Valve Guide:

- Yes, Machine*
- No, do not Machine*

Install Valve Seats:

- Install Seats*
- Include Seats but Don't Install*

Install Valve Guides:

- Install Guides (defaulted if yes is chosen for install valve seats)*
- Include Guides but Don't Install*

Spring Type:

- 90-2082 .800" Triple Titanium*
- No Springs (Valves Included)*
- No Springs – No Valves*

Compression Release Machining:

- Yes, Machine*
- No, do not Machine*

Spark Plug Holes:

- Single Plug*
- Dual Plugs (Option only if no to compression release machining)*
- Street Pro (12mm Primary Side/10mm Cam Side)*
- None*

Fire Ring Machining:

- Specify*
- No Fire Ring*
- Standard Fire Ring*

Fire Ring Diameter: (Only answer if specify fire ring machining is chosen)

- 0.000 – 5.400" _____ specify*

Fire Ring Depth: (Only answer if specify fire ring machining is chosen)

- 0.000 – 0.250" _____ specify*

Comments: _____

